

Technical Specifications

Model S4010AP	DK289A
Processor & Speed	2.4 GHz/400 Intel® Celeron™ Processor – PGA478
Chipset	Intel® 845GL
Motherboard	P4GS33-LA-GLA
RAM	256/2100 MB DDR SDRAM
Maximum	1 GB (2x512MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256 and 512 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 128 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-RW Drive: 48x-Write / 12X-Re-write/CD-ROM speed =48x max.
Average Random Access	110ms
Transfer Rate	6.0MB/sec.
Diskette Drive	3.5" (1.44MB)
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	Intel® Extreme Graphics
Controller	Integrated w/845G Chipset
Video Memory	Dynamic up to 48MB UMA
Network Card	10/100 BaseT, Integrated
MPEG-1/2	MPEG-1 for full-screen, full-motion digital video
Sound	AC'97 Integrated on MB
Controller	Realtek ALC202A
Chassis	Chameleon, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel
Front I/O Connector	2= USB
Expansion Slots (Total)	3= PCI
Expansion Slots (FREE)	1= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse